

# FKD单缸液压圆锥破碎机

## FKD Single Cylinder Hydraulic Cone Crusher



### 设备特点 Features

- 1.特殊的破碎腔型、合理的偏心量,理想的摆频及层压缩破碎带来更高的产量,更大的破碎比,更优的粒形。
- 2.坚固的设备结构及先进的过载保护系统,可确保在最恶劣的硬岩石破碎应用中长期运行,发生故障率较低。
- 3.正压防尘系统保证润滑系统时刻洁净,使设备在运行时免受灰尘的污染,且不需要增加额外的润滑密封及人工维护。
- 4.自动化程度高,操作简单。
- 5.设备维护方便,大部分部件均能在上部及侧部拆装,可降低工人劳动强度,提高施工效果。
- 6.特殊的破碎壁,轧臼壁设计,极大减少用户对备件的投资。

1. Special crushing cavity type, reasonable eccentricity, ideal swing frequency and layer compression crushing bring higher output, larger crushing ratio, and better grain shape.
2. The sturdy equipment structure and advanced overload protection system can ensure long-term operation in the worst hard rock crushing applications, with a low failure rate.
3. The positive pressure dustproof system ensures that the lubrication system is always clean, so that the equipment is protected from dust pollution during operation, and no additional lubrication seals and manual maintenance are required.
4. High degree of automation and simple operation.
5. The equipment is easy to maintain, most parts can be disassembled on the upper and side, which can reduce the labor intensity of workers and improve the construction effect.
6. Special broken wall and mortar wall design greatly reduce the user's investment in spare parts.

型号 Model	功率 Power (kw)	腔型 Chamber Type	最大进料粒度 Max Feedin Size (mm)	紧边排料口下的标准产能 CSS Discharge Opening & Standard Capacity (t/h)											
				6	8	10	13	16	19	22	25	32	38	44	51
FKD-44	220	特粗 Extra thick	217	-	-	-	-	115-202	123-279	132-297	140-316	160-360	177-399	-	-
		粗 Crude	177	-	-	-	102	110-220	118-295	126-316	135-336	153-382	169-339	-	-
		中粗 Medium thick	142	-	-	-	98-124	107-266	105-286	122-305	130-325	148-333	163-245	-	-
		中 Medium	112	-	-	-	119-190	128-283	138-303	148-324	157-345	179-286	198	-	-
		中细 Medium fine	87	-	-	117	127-237	137-251	147-269	157-288	167-306	190-254	-	-	-
		细 fine	72	-	83-139	99-181	107-196	115-212	123-227	133-243	141-258	160-214	-	-	-
		特细 Extra fine	40	100	125	-	-	-	-	-	-	-	-	-	-
FKD-53	315	特粗 Extra thick	280	-	-	-	-	180	193-344	207-444	220-472	250-557	277-616	303-674	334-520
		标准粗 Standard coarse	250	-	-	-	-	178-198	191-382	204-498	216-530	247-604	273-667	299-532	330-361
		粗 Crude	220	-	-	-	-	175-194	188-376	201-491	214-522	244-596	269-658	295-524	324-361
		中粗 Medium thick	180	-	-	-	-	167-260	179-438	191-468	204-498	232-568	256-513	281-374	-
		中 Medium	140	-	-	-	-	204-306	219-456	234-487	249-519	284-521	313-418	-	-
		中细 Medium fine	120	-	-	-	200	216-385	232-413	247-441	263-470	299-471	332-379	-	-
		细 fine	90	-	-	-	206-320	222-347	238-373	255-398	271-424	309-425	342	-	-
特细 Extra fine	70	-	-	-	227-316	244-340	263-321	281-312	-	-	-	-	-		
FKD-870	500		80-330	1、排料口调整范围 (Adjustment Range Of Discharge Opening) 10-60mm 2、产量 (Capacity) 500-1200t/h 3、机重 (Weight) 59t											

型号 Model	功率 Power (kw)	腔型 Chamber Type	最大进料粒度 Max Feedin Size (mm)	紧边排料口下的标准产能 CSS Discharge Opening & Standard Capacity (t/h)											
				19	22	25	29	32	35	38	41	44	48	51	
FKD-44S	250	特粗 Extra thick	400	-	-	-	-	-	267	282-353	298-446	313-563	334-601	349-534	
		粗 Crude	350	-	-	-	225	239-299	254-381	269-484	284-511	298-448	318-398	333	
		中粗 Medium thick	300	-	-	195	214-267	228-342	242-435	256-461	270-486	284-426	303-378	317	

型号 Model	功率 Power (kw)	腔型 Chamber Type	最大进料粒度 Max Feedin Size (mm)	紧边排料口下的标准产能 CSS Discharge Opening & Standard Capacity (t/h)											
				38	41	44	48	51	54	60	64	70	76	83	
FKD-53S	315	特粗 Extra thick	450	-	349	368-460	392-588	410-718	428-856	456-929	489-978	525-1050	562-983	604	
		粗 Crude	400	318	336-420	353-618	376-753	394-788	411-823	446-892	469-822	504-631	-	-	

注:规格型号如有变动,恕不另行通知。  
Note: Specifications and models are subject to change without notice.